

## Drover



Photo may contain optional equipment

## Drover

Steel slant load gooseneck horse trailer with front slant tack room and plexiglass side enclosures in horse area

### Standard Features

#### Available sizes

- 2-HORSE gooseneck, 13' floor length w/2-3500# axles, 15" tires & 6-hole wheels
- 3-HORSE gooseneck, 16' floor length w/2-3500# axles, 15" tires & 6-hole wheels
- 3-HORSE gooseneck, 16' floor length w/2-5200# axles, 15" tires & 6-hole wheels
- 4-HORSE gooseneck, 20' floor length w/2-5200# axles, 15" tires & 6-hole wheels
- 5-HORSE gooseneck, 24' floor length w/2-7000# axles, 16" tires & 8-hole wheels
- 2-HORSE gooseneck, 13' floor length w/2-5200# axles, 15" tires & 6-hole wheels (6'-8" models)
- 3-HORSE gooseneck, 16' floor length w/2-5200# axles, 15" tires & 6-hole wheels (6'-8" models)
- 4-HORSE gooseneck, 20' floor length w/2-6000# axles, 16" tires & 8-hole wheels (6'-8" models)
- 5-HORSE gooseneck, 24' floor length w/2-7000# axles, 16" tires & 8-hole wheels (6'-8" models)

#### Dimensions

- 6'-6" body height
- 6' or 6'-8" body width, (6'-8" has no wheel well, 102" overall)
- 7' gooseneck length

#### Undercarriage

- Rubber torsion axles with four wheel independent suspension and greasable hubs for easy lubrication
- Electric brakes on all wheels
- Radial tires on silver modular wheels with chrome center caps
- Spare tire, wheel and rack

#### Coupler & Jacks

- Adjustable hitch stem with 2-5/16" coupler and safety chains with hooks
- Heavy duty low profile gooseneck structure
- Single speed drop-leg jack
- Emergency breakaway system: switch, cable and battery box complete with battery (less charger)

#### Design Features & Hardware

- Low profile 6" radius corner galvanized roof
- All steel frame with formed galvanized side panels
- Tapered nose with radius corners for aerodynamics, (6' models), 6' to 54" (6'-8" models) 6'-8" to 60"
- 52" sides with air spaces above
- Treated floor
- Steel hold backs on all full height doors
- Slide-in plexiglass to cover air spaces on both sides
- Greasable exterior hinges
- Tag bracket
- Chrome trim with colored vinyl insert
- Pin striping (upper and lower region only)

#### Stall Area Equipment

- Removable slant tubing dividers (per two stalls) with solid head partition
- Quick release slam latches on all dividers
- Rubber interior kick mat wall lining (1/4" thick), located on butt wall only with 3/4" plywood underneath
- Vet type rubber floor mats (5/8" thick)
- One-piece rear door matches sides with hold back
- Side access door in first stall on street side
- Feed bag rings (3 per stall)
- Interior and exterior tie rings
- Removable breast strap (located at first stall access door)

#### Lights

- DOT required lighting (stop, turn, tail, tag, marker, clearance & conspicuity tape)
- Dome lights (one in tack room and one in stall area)
- All dome lights and loading lights are on a separate circuit

#### Front Tack Room Equipment

- Dimensions: 2' to 6'6" x 6' wide plus 7' gooseneck or 2' to 6'6" x 6'-8" wide plus 7' gooseneck
- Full height partition wall between stalls and front tack room
- Full size access door with recessed locking handle 31-1/4" x 71" (6'-6" tall model) located on curb side
- Four saddle racks on a tree and bridle hooks in tack room
- Brush tray
- Blanket bar