

Odyssey



Photo may contain optional equipment

Odyssey

Aluminum exterior with steel frame two horse straight load bumper pull trailer with feed manger and tack compartment

Standard Features

Available sizes

2-HORSE bumper pull, 11' floor length w/2-3500# axles, 15" tires & 5-hole wheels

Dimensions

6'-6" body height
6' body width
7' stall length with three butt strap settings
24" tongue length

Undercarriage

Rubber torsion axles with four wheel independent suspension and greasable hubs for easy lubrication
Electric brakes on all wheels
Radial tires on silver modular wheels with chrome center caps

Coupler & Jacks

2" coupler and safety chains with hooks
Top-wind jack with caster wheel
Emergency breakaway system: switch, cable and battery box complete with battery (less charger)

Design Features & Hardware

Low profile 6" radius corner aluminum roof
All steel tubular frame and side structure with .050 pre-painted white aluminum side panel
Double lined smooth galvalume walls in horse area with 1-1/2" styrofoam insulation
Aluminum framed drop-down feed door with radius corner sliding window at each horses' head
Wedge nose
Treated floor
Rubber bumper on rear
Bolt-on aluminum mill finish fenders
Aluminum tread plate gravel guard
AE graphic package
Tag bracket

Stall Area Equipment

19" x 53" large radius corner sliding window on each side of stall area with safety bars
14" x 16" radius corner sliding window and safety bars in each rear door with hold backs on each door
Solid half divider with padding and a solid head and shoulder partition
Stall area lined with side padding and breast padding
Rubber kick mats on rear doors and side walls
Vet type rubber floor mats (5/8" thick)
Side access door on each side
Removable rear post
Aluminum two-way flip-up roof vent over each horse
Interior and exterior tie rings
Butt straps

Lights

DOT required lighting (stop, turn, tail, tag, marker & clearance)
Dome lights (one at center in rear to enhance stall lighting and one in center of tack compartment)
Two rear exterior loading lights above rear doors
Four tail lights

All dome lights and loading lights are recessed and on a separate circuit

Front Tack Compartment Equipment

Tack compartment carpeted with feed manger above
Locking tack doors with an individual carpeted swing-out saddle rack on each side
Bridle hooks in tack compartment